



List of Significant Intersections - RW and South Wall Zones, Glacier Creek Prospect

Drill Hole	From (feet)	To (feet)	Intercept (feet)	Intercept (meters)	Cu %	Zn %	Pb %	Ag (g/t)	Au (g/t)	Zone
<i>Includes</i>	470.5	487	16.5	5.03	0.22	1.53	0.95	84.9	0.92	RW Zone (Oxide)
CMR09-24	1043.7	1105	61.3	18.68	1.16	4.15	0.1	30.7	0.3	SW Zone I
<i>Includes</i>	1043.7	1073.4	29.7	9.05	1.89	5.16	0.02	27.4	0.3	SW Zone I
CMR09-25	488.9	508.5	19.6	5.97	0.1	1.47	<0.01	0.5	0.01	secondary Cu-Zn
CMR09-25	1104	1159.2	55.2	16.82	0.11	1.41	0.03	13.3	0.16	SW Zone I
<i>Includes</i>	1142	1159.2	17.2	5.24	0.06	0.78	0.04	25.5	0.31	SW Zone I
CMR09-26	909.1	911.5	2.4	0.73	0.05	1.19	0.46	40.3	0.08	SW Zone III
CMR09-26	1052	1072	20	6.1	1.52	9.17	0.02	18	0.18	SW Zone II
<i>Includes</i>	1055.1	1068.2	13.1	3.99	2.09	9.19	0.02	22	0.22	SW Zone II
<i>Includes</i>	1059.4	1068.2	8.8	2.68	3.17	8.06	0.02	29.4	0.3	SW Zone II
CMR09-27						<i>No significant intersection</i>				
CMR09-28	1148.8	1156.3	7.5	2.29	3.55	4.69	0.05	80.1	0.28	SW Zone III
<i>Includes</i>	1151.5	1155	3.5	1.07	6.12	5.81	0.03	123.9	0.48	SW Zone III
CMR09-29	65	81.5	16.5	5.03	0.22	1.82	<0.01	0.5	<0.01	secondary Cu-Zn
CMR09-29	629	686.8	57.8	17.62	0.02	0.55	0.04	1.7	0.02	Zn-stringers
CMR09-30	294	335	41	12.5	0.13	0.52	0.94	74.5	0.39	RW Zone (Oxide)
<i>Includes</i>	297	320	23	7.01	0.2	0.42	1.23	104.1	0.57	RW Zone (Oxide)
<i>Includes</i>	302	310	8	2.44	0.35	0.64	2.45	178.1	1.03	RW Zone (Oxide)
CMR09-30	495	520.7	25.7	7.83	0.13	2.65	<0.01	0.6	0.01	secondary Cu-Zn
CMR09-30	564.3	597	32.7	9.97	0.29	0.34	0.01	2.4	0.04	low grade stringers
CMR09-30	1635	1750	115	35.05	0.02	0.7	0.01	0.5	0.01	low grade stringers
<i>Includes</i>	1635	1650	15	4.57	0.02	2.61	0.01	0.8	0.01	low grade stringers
CMR09-31	1180.5	1191.7	11.2	3.41	0.18	1.98	0.07	8.7	0.01	SW Zone III
CMR09-32	800.2	804.5	4.3	1.31	0.06	3.13	0.13	3.2	0.07	SW Zone III
CMR10-33	531.5	539.5	8	2.45	0.07	4.84	0.08	19.6	0.19	RW Zone (a)
<i>Includes</i>	531.5	537.4	5.9	1.8	0.08	5.95	0.06	21.1	0.2	RW Zone (a)
CMR10-33	623.7	645.1	21.5	6.54	0.48	0.28	0.05	8.1	0.08	stringers
CMR10-33	691.9	801.5	109.6	33.4	0.02	0.63	0.02	0.8	0.03	stringers
<i>Includes</i>	788.5	798.2	9.7	2.95	0.04	3.45	0	0.9	0.01	stringers
CMR10-34B	985.9	1020	34.1	10.4	0.3	4.18	0.42	81.6	0.87	SW Zone I
CMR10-35	371.6	372	0.5	0.15	0.01	14.15	1.84	272	0.12	RW Zone
CMR10-35	451.8	475.1	23.3	7.1	2.1	1.52	0.01	16.8	0.18	RW Zone
<i>Includes</i>	461.5	475.1	13.6	4.15	3.13	0.62	<0.01	23.9	0.23	RW Zone
CMR10-35	475.1	566.9	91.9	28	0.13	0.52	0.02	1.5	0.05	stringer
CMR10-36					<i>No significant intersection</i>					
CMR10-37	442.9	470.5	27.6	8.4	0.39	0.34	<0.01	1.8	0.05	stringer
<i>Includes</i>	442.9	449.1	6.2	1.9	0.91	0.27	<0.01	4.1	0.09	stringer
CMR10-38	86	175.2	89.2	27.2	0.13	0.63	0.96	115.5	0.88	RW Zone (Oxide)
<i>Includes</i>	86	96.5	10.5	3.2	0.26	3.52	2.28	131.1	1.13	RW Zone (Oxide)
CMR10-38	188.6	416	227.4	69.3	0.16	1.17	<0.01	1.3	0.02	secondary Cu-Zn
<i>Includes</i>	214.9	330.1	115.2	35.1	0.18	1.68	<0.01	0.9	0.01	secondary Cu-Zn
CMR10-38B	86.6	164.7	78.1	23.8	0.36	2.94	0.96	123.1	0.82	RW Zone (Oxide)
<i>Includes</i>	86.6	119.9	33.3	10.15	0.7	6.51	1.02	89.7	0.39	RW Zone (Oxide)
CMR10-38B	185	195	10	3.05	1.6	1.00	0.01	8.4	0.01	secondary Cu-Zn
<i>Includes</i>	185	190	4.9	1.5	2.66	1.29	0.01	3.1	0.01	secondary Cu-Zn
CMR10-39	1424.5	1469.8	45.3	13.8	0.34	1.36	0.01	8.1	0.05	SW Zone III
<i>Includes</i>	1425.9	1433.9	8	2.45	1.1	4.52	0	24.8	0.13	SW Zone III
<i>Includes</i>	1428	1430.1	2.1	0.65	3.3	9.29	0	75.4	0.4	SW Zone III
CMR10-40	508.2	576.4	68.2	20.8	1.03	5.01	0.04	11.3	0.14	SW Zone I
<i>Includes</i>	515.9	555.4	39.5	12.05	1.41	6.13	0.02	14.4	0.17	SW Zone I
CMR10-41					<i>No significant intersection</i>					
CMR10-42	638.5	694.9	56.4	17.2	0.18	1.24	0.01	2.8	0.04	SW Zone III
CMR13-43	700.7	783.4	82.8	25.23	1.17	0.43	<0.01	8.5	0.07	SW Zone I
<i>Includes</i>	748.6	783.4	34.9	10.63	1.77	0.27	<0.01	13.8	0.15	SW Zone I
CMR13-44	535.5	546.5	11	3.36	0.51	9.18	0.92	46.2	0.21	RW Zone
<i>Includes</i>	539.4	544.4	4.9	1.5	0.82	15.05	1.52	76.2	0.34	RW Zone
CMR13-45	469.3	540.6	71.2	21.71	2.36	9.06	0.13	28.8	0.33	SW Zone I
<i>Includes</i>	470.8	509.8	39	11.88	3.29	10.48	0.12	35.5	0.44	SW Zone I
CMR13-46	684	751.5	67.5	20.58	0.92	7.18	0.25	45.3	0.32	SW Zone II
<i>Includes</i>	684	726.3	42.3	12.9	0.83	10.26	0.37	63.3	0.44	SW Zone II
CMR13-47	655.2	672.1	16.8	5.13	0.05	2.62	0.11	9	0.08	RW Stringer
CMR13-48					<i>No significant intersection</i>					



List of Significant Intersections - RW and South Wall Zones, Glacier Creek Prospect

Drill Hole	From (feet)	To (feet)	Intercept (feet)	Intercept (meters)	Cu %	Zn %	Pb %	Ag (g/t)	Au (g/t)	Zone	
CMR13-49	469.6	550.5	80.9	24.66	2.02	8.47	0.06	31.7	0.51	SW Zone I	
CMR13-49	838.9	861.5	22.5	6.86	0.5	3.75	0.06	10.5	0.09	SW Zone II	
<i>Includes</i>	855.2	861.5	6.3	1.91	0.61	6.13	0.04	13.5	0.11	SW Zone II	
CMR13-49	974.5	983.3	8.8	2.67	0.01	4.73	0.34	6.9	0.02	SW Zone III	
CMR13-50	79	202	123	37.49	0.53	2.35	1.21	123.2	0.62	RW Zone (Oxide)	
<i>Includes</i>	79	124	45	13.72	0.51	4.97	1.61	134.3	0.71	RW Zone (Oxide)	
CMR13-51						<i>No significant intersection</i>					
CMR13-52						<i>No significant intersection</i>					
CMR14-53	1686.4	1689.6	3.3	1.0	0.36	5.46	0.30	18.5	0.07	SW Zone II	
CMR14-53	1706.7	1715.2	8.5	2.6	1.53	1.34	0.01	18.0	0.10	SW Zone II	
CMR14-54	1659.4	1732	72.5	22.1	2.48	4.05	0.02	24.0	0.39	SW Zone II (EM)	
<i>Includes</i>	1659.4	1685	25.6	7.8	0.76	7.51	0.03	26.4	0.40	SW Zone II (EM)	
<i>Includes</i>	1685	1714.2	29.2	8.9	3.76	3.23	0.01	27.4	0.42	SW Zone II (EM)	
CMR14-55						<i>No significant intersection</i>					
CMR14-56						<i>anomalous cuttings @ end of hole (e.g. 84.4 g/t Ag, 0.55% Zn)</i>					Abandoned
CMR14-57						<i>No significant intersection</i>					
CMR14-58	2289.7	2299.2	9.5	2.9	0.08	5.62	0.01	2.0	0.01	footwall stringer	
CMR14-58	2539.4	2541.3	2	0.6	2.79	0.04	0.01	13.2	0.18	Stringer	
CMR14-59	991.8	1042.3	50.5	15.4	1.03	2.88	0.03	21.0	0.16	SW Zone II	
<i>Includes</i>	991.8	1005.9	14.1	4.3	0.62	4.80	0.02	23.8	0.21	SW Zone II	
<i>Includes</i>	1020.7	1042.3	21.7	6.6	1.62	2.89	0.04	27.2	0.19	SW Zone II	
CMR14-60						<i>No significant intersection</i>					
CMR14-61						<i>No significant intersection</i>					
CMR14-62	2553.8	2566.3	12.5	3.8	0.05	2.23	0.13	4.1	0.08	footwall stringer	
CMR14-63	1535.8	1597.1	61.3	18.7	0.1	1.85	0.10	17.5	0.09	SW Zone III (EM)	
<i>Includes</i>	1535.8	1541	5.2	1.6	0.21	5.69	0.33	58.4	0.35	SW Zone III (EM)	
CMR14-63	1640.1	1647	6.9	2.1	0.40	8.22	0.11	33.1	0.65	SW Zone II (EM)	
CMR14-64	2159.1	2215.6	56.5	17.2	0.21	3.49	0.02	15.3	0.08	SW Zone III (EM)	
<i>Includes</i>	2202.1	2215.6	13.5	4.1	0.55	4.98	0.02	21.1	0.16	SW Zone III (EM)	
CMR14-65	1355.0	1647.0	292	89	0.79	5.03	0.05	21.1	0.31	SW Zone II (EM)	
<i>Includes</i>	1355.0	1405.5	50.5	15.4	0.51	7.92	0.12	51.4	0.32	SW Zone II (EM)	
<i>Includes</i>	1493.1	1615.8	122.7	37.4	1.22	5.96	0.02	20.3	0.51	SW Zone II (EM)	
<i>Includes</i>	1493.1	1580.4	87.3	26.6	1.03	7.84	0.02	21.1	0.51	SW Zone II (EM)	
<i>Includes</i>	1556.1	1580.4	24.3	7.4	2.05	10.23	0.02	34.3	1.13	SW Zone II (EM)	
CMR14-66	2049.9	2063	13.1	4	0.07	4.27	0.18	11.8	0.08	SW Zone III (EM)	
CMR14-66	2111.5	2148.6	37.1	11.3	0.3	3.95	0.28	27.2	0.23	SW Zone II (EM)	
<i>Includes</i>	2111.5	2116.5	4.9	1.5	0.21	7.01	1.45	128.4	0.87	SW Zone II (EM)	
<i>Includes</i>	2128.6	2136.5	7.9	2.4	0.19	6.45	0.04	5.8	0.12	SW Zone II (EM)	
<i>Includes</i>	2144.4	2148.6	4.3	1.3	0.89	7.71	0.01	12.8	0.23	SW Zone II (EM)	
CMR14-67	397	447.2	50.2	15.3	0.13	3.12	0.24	30.7	0.14	RW Zone	
<i>Includes</i>	400.3	413.1	12.8	3.9	0.19	5.11	0.63	92.5	0.37	RW Zone	
CMR14-68						<i>No significant intersection</i>					

Drill intercepts reported as core lengths are estimated to be 50-100% true width. Bold text denotes intervals at >2 meters at >2% copper and/or 10% zinc OR >20 meters at >1% copper and/or 5% zinc and/or 100 g/t Ag. Averages are length x density weighted using density data obtained for each sample within a given interval (where density data is available). Length x density averages more accurately represent the metal content of a given interval, and is common practice in reporting on massive sulphide deposits because of the wide range of densities they exhibit. The Company has adopted length x density weighting as standard procedure for this project. For QAQC and other sample related procedures please visit the Company's technical report entitled, "Palmer VMS Project, Southeast Alaska, Mineral Resource Estimation and Exploration Update" dated March 4, 2010 and available on www.sedar.com. Darwin Green, VP Exploration for Constantine Metal Resources Ltd. and a qualified person as defined by Canadian National Instrument 43-101 has reviewed and verified the information within this table.